



PERFORMANCE

Delivered Lumens 2400 lm
Power Consumption 30W
Luminous Efficacy 80lm/W
90 CRI
Full detail in photometry summary

CERTIFICATION

UL Listed
UL Listed to Canadian safety standards.
Suitable for Damp Locations

SUSPENSION

White 5" round flat canopy
Standard 72" cable
Standard Hang Height 65"
Minimum Hang Height 30"
Cable extension available (up to 420")
Field trimmable

LED LIFESPAN

50k hours

SPECIFICATION LOGIC

PRIMARY FINISH

Table with 2 columns: Finish Name and Code. Rows include Matte White (PC20), Silk Grey (PC25), Ochre Yellow (PC26), Matte Black (PC30), Vermilion (PC42), and Custom Powder Coated (PCXX).

COLOR TEMPERATURE

Table with 2 columns: Color Temperature and Code. Rows include 2700K (warm white) (27), 3000K (soft white) (30), 3500K (neutral white) (35), and 4000K (cool white) (40).

DIMMING / CONTROL / INPUT

Table with 2 columns: Dimming/Control/Input and Code. Rows include 0.1% Dimming (0.1_10V_UNV), 1% Dimming TRIAC (1_TRIAC_120V), and 1% Dimming (1_10V_UNV).

DRAWINGS

CTP-18 Centro Pendant Dimension

128 [5 in]

Centro Pendant

Pendants

YOUR PRODUCT CODE

CTP- [] - [] - [] - [] - []

DESCRIPTION

Centro, a sleek, circular fixture for both flushmount and pendant installation. With its slim profile and light-diffusing perforated edge, Centro possesses a subtle sophistication other fixtures don't.

MATERIALS

Powder coated steel, acrylic diffuser

PRODUCT DIMENSIONS

18 in dia x 5 in H

PRODUCT WEIGHT

4.6 kg

ase
:ept
kies
see
is
tent

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies. Cookie Policy

CUSTOMIZE

ACCEPT ALL