


# CONTOUR — CW

A—N—D

CEILING/WALL

Designed by Lukas Peet

2025



**CANOPY**  
STANDARD  
SURFACE  
MOUNT

Ø 15cm | 6"



14cm  
5.5"

Ø 15cm | 6"



20.5cm  
8"

Ø 22.5cm | 8.75"



27cm  
10.75"

Ø 30cm | 11.75"

**CANOPY**  
MINI  
FLUSH  
MOUNT

Ø 8cm | 3.25"



13cm  
5.25"

Ø 15cm | 6"



19.5cm  
7.75"

Ø 22.5cm | 8.75"



26cm  
10.25"

Ø 30cm | 11.75"

CON-225-CW-SL-27-UNV-120/277-STN

A-N-D.COM

## TYPE

Ceiling/Wall

## MATERIALS

Glass, Aluminum

## MANUFACTURED

Canada

## DIMENSIONS

### Standard Surface Mount

150: Ø 15cm x 14cm / Ø 6" x 5.5"

225: Ø 22.5cm x 20.5cm / Ø 8.75" x 8"

300: Ø 30cm x 27cm / Ø 11.75" x 10.75"

### Mini Flush Mount

150: Ø 15cm x 13cm / Ø 6" x 5.25"

225: Ø 22.5cm x 19.5cm / Ø 8.75" x 7.75"

300: Ø 30cm x 26cm / Ø 11.75" x 10.5"

## TECHNICAL INFORMATION

### Input Voltage

110–277V, 220–240V

### Lamping

Integral 10W LED

CRI 90+, 50,000 hours

### Controls

TRIAC/0–10V, DALI

## FINISHES



Pearl (PL)



Slate (SL)



Citrine (CI)



For custom finishes, please inquire.

## MOUNTING OPTIONS

–Standard Surface Mount


(Junction box mount)

–Mini Flush Mount (Remote only)

–See install instructions for more details


## DIM TO WARM

Warm / DIM - Bright / DIM +



## COLOUR TEMPERATURE

Warm Neutral



## 3D MODELS ON A-N-D.COM

REVIT, IES, DWG, 3DS, Rhino, Sketchup

## CERTIFICATIONS



Application: dry indoor location only

SERIES	SIZE	TYPE	FINISH	CCT	PS	VOLTAGE IN	CANOPY
CON	<input type="checkbox"/> 150	CW	<input type="checkbox"/> PL (PEARL)	<input type="checkbox"/> 27 (2700K)	<input type="checkbox"/> UNV	<input type="checkbox"/> 120/277	<input type="checkbox"/> STN (STANDARD)
	<input type="checkbox"/> 225		<input type="checkbox"/> SL (SLATE)	<input type="checkbox"/> DW (DIM TO WARM)	<input type="checkbox"/> DAL	<input type="checkbox"/> 230	<input type="checkbox"/> MIN (MINI)
	<input type="checkbox"/> 300		<input type="checkbox"/> CI (CITRINE)				