



# Crisp Sconce

Sconces

## YOUR PRODUCT CODE



## DESCRIPTION

Crisp's simple, iconic design is suitable for both wall and ceiling installation, indoors and outdoors. The solid glass shade, offered in a range of finishes, is distinguished by its scored surface, adding a subtle textural detail to the environment.

## MATERIALS

Cast solid glass, aluminum

## COLLECTION NOTES

Luminaire lumens listed are for AC input TRIAC control. DC input performance please see photometry downloads. Each form of cast glass is unique. We review each to ensure they conform to ASTM standards, which includes the presence of small air bubbles within the glass.

## PRODUCT DIMENSIONS

5 in dia x 3.3 in D

## PRODUCT WEIGHT

3.5 lbs / 2 kg

## PERFORMANCE

Delivered Lumens 550 lm (Frosted) | 445 lm (White) | 106 lm (Chrome) | 52 lm (Copper)  
Power Consumption 7.5W  
Luminous Efficacy 71.7 lm/W (Frosted) | 58.1 lm/W (White) | 13.9 lm/W (Chrome) | 6.9 lm/W (Copper)  
90 CRI  
Full detail in [photometry summary](#).

## CERTIFICATION

ADA Compliant  
UL Listed  
UL Listed to Canadian safety standards.  
Suitable for Wet Locations  
Suitable for Damp Locations  
IP20  
IP65  
Declare (LBC Red List Approved)

## Declare.

## LED LIFESPAN

50k hours

## SPECIFICATION LOGIC

### GLASS FINISH

|                 |     |
|-----------------|-----|
| White Interior  | S10 |
| Chrome Exterior | S11 |
| Frosted         | S12 |
| Copper Exterior | S13 |

### BACKPLATE FINISH

|                  |      |
|------------------|------|
| Natural Anodized | AA01 |
| Black Anodized   | AA04 |

### COLOR TEMPERATURE

|                       |    |
|-----------------------|----|
| 2700K (warm white)    | 27 |
| 3000K (soft white)    | 30 |
| 3500K (neutral white) | 35 |

### DIMMING / CONTROL / INPUT

|  |               |
|--|---------------|
| High Output, 1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)   | 10V_UNV       |
| High Output, 0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External) | 0.1V_UNV      |
| 10% Dimming, TRIAC / Forward Phase Control, 120V Input                                     | 10_TRIAC_120V |
| 1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)                    | 1_TRIAC_120V  |
| 1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)                | 1_10V_UNV     |
| 0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)              | 0.1_10V_UNV   |
| Low Voltage (Driver required, driver not included)   | LV            |

## DRAWINGS

|                              |      |
|------------------------------|------|
| IP 20                        | IP20 |
| CR-WS Crisp Sconce Dimension | IP65 |

