



PERFORMANCE
800 lumens (estimated)
Power Consumption 17.13W

CERTIFICATION
UL Listed
UL Listed to Canadian safety standards.
IP20

LED LIFESPAN
50k hours

SPECIFICATION LOGIC

FELT FINISH

Graphite	FC01
Sand	FC03
Umber	FC04

CCT

2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35
4000K (cool white)	40

DIMMING / CONTROL / INPUT

1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	1_TRIAC_120V
1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	1_10V_UNV
Low Voltage (Driver required, driver not included)	LV

IP RATING

IP 20	IP20
-------	------

Highline Flush Mount

Ceiling Flush Mounts

YOUR PRODUCT CODE

HLFM- - - - -
- - - - -

DESCRIPTION

Highline steps into its own as a standalone flush mount and pendant, distilling its precision into a singular, pragmatic form. Designed in collaboration with industrial designer Jonas Damon, this iteration brings the original linear pendant's clean lines and minimalist elegance to a pragmatic pendant. With meticulous detailing and a focus on function, Highline's independent fixture offers sleek, elevated illumination—designed to stand out without overpowering.

MATERIALS

LLDPE, Aluminum, Molded Felt

PRODUCT DIMENSIONS

14 in dia x 6 in H

DRAWINGS

Highline flush mount dimensional drawing

