



PERFORMANCE

Delivered Lumens 340 lm
Power Consumption 8.9W
Luminous Efficacy 38.2 lm/W
90 CRI
Full detail in [photometry summary](#)

CERTIFICATION

UL Listed
UL Listed to Canadian safety standards.
Suitable for Damp Locations

PATENT FILE NUMBER

US: D900,373, CA: 188813, EU: 006641924-0001,
UK: GB90066419240001

LED LIFESPAN

50k hours

SPECIFICATION LOGIC

PRIMARY FINISH

Matte White	PC20
Matte Black	PC30
Vert Clair	PC43
Buff	PC44
Custom Powder Coat	PCXX

COLOR TEMPERATURE

2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

DIMMING / CONTROL / INPUT

0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	0.1_10V_UNV
10% Dimming, Touch Control, 120V Input	10_TOUCH_120V
1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	1_10V_UNV
1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	1_TRIAC_120V
Low Voltage (Driver required, driver not included)	LV

DRAWINGS

MNT Monocle Touch Sconce Dimension



Monocle

Sconces

YOUR PRODUCT CODE

MNT- - - - -

DESCRIPTION

Monocle-a sleek, rotating sconce, with dimming control at the touch of a finger. Touch to cycle three levels of light, on, and off. Monocle's pleasantly round demeanor and touch dimmer makes it an ideal lamp for a bedside or workstation.

MATERIALS

Cast aluminum, steel, TPE cord, molded plastic

PRODUCT DIMENSIONS

6 W x 5 H x 4 in D

PRODUCT WEIGHT

2.2 lbs / 1 kg

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies. [Cookie Policy](#)

CUSTOMIZE

ACCEPT ALL