



# Pastille 1 Collar

Sconces

## YOUR PRODUCT CODE

PAS-1S- - - - -  
- -

## DESCRIPTION

Pastille's design echoes the Art Deco sensibilities of Old Hollywood. The collection offers mix-and-match options for custom installation, including either a droplet profile or faceted pattern for the glass globe, with various finishes for an accent ring or backplate.

## MATERIALS

Opal glass, aluminum or steel plate

## COLLECTION NOTES

This product is designed to be installed on a 4" round or octagonal junction box. Custom hand painting and braille solutions are available for the Pastille collection. Inquire with sales@rbw.com.

## PRODUCT DIMENSIONS

5 in dia x 4 in D

## PRODUCT WEIGHT

1 lbs / 0.5 kg

## PERFORMANCE

Delivered Lumens 430 lm  
Power Consumption 7.5W  
Luminous Efficacy 57.5 lm/W  
90 CRI  
Full detail in [photometry summary](#)

## CERTIFICATION

ADA Compliant  
UL Listed  
UL Listed to Canadian safety standards.  
Suitable for Damp Locations  
IP20  
IP65

## PATENT FILE NUMBER

US: D935,085, D970,788, D1012346, D1020048,  
CA: 187451, EU: 006433652-0001, UK:  
GB90064336520002

## LED LIFESPAN

50k hours

## SPECIFICATION LOGIC

### DIFFUSER STYLE (GLOBE)

Droplet	D
Faceted	F
Ribbed	R

### PRIMARY FINISH COLOR

Matte White	PC20
Silk Grey	PC25
Matte Black	PC30
Breccia	PC31
Vermilion	PC42
Custom Powder Coated	PCXX
Polished Chrome	PF13
Satin Brass	PF17

### COLOR TEMPERATURE

2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

### DIMMING / CONTROL / INPUT

10% Dimming, TRIAC / Forward Phase Control, 120V Input	10_TRIAC_120V
1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	1_TRIAC_120V
1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	1_10V_UNV
0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	0.1_10V_UNV
Low Voltage (Driver required, driver not included)	LV

### IP RATING

IP 20	IP20
IP 65	IP65

## DRAWINGS

PAS-1S Pastille Collar Sconce Dimension

