



**PERFORMANCE**

Estimated Lumens 1210 DC, 940 AC  
 90 CRI  
 Power Consumption 15.96W

**CERTIFICATION**

ADA Compliant  
 UL Listed  
 UL Listed to Canadian safety standards.  
 Suitable for Damp Locations  
 IP20  
 IP65

**LED LIFESPAN**

50k hours

# Pastille 2

Sconces

**YOUR PRODUCT CODE**



**DESCRIPTION**

A fresh chapter in RBW's celebrated Pastille lineup, Pastille 2 reimagines modular lighting with effortless elegance. Inspired by organic forms and architectural precision, its dual-globe design offers a sculptural, versatile solution that balances bold aesthetics with pragmatic functionality.

**MATERIALS**

Opal Glass, Aluminum Plate

**PRODUCT DIMENSIONS**

12.5 L x 5.5 W x 4 in D

**PRODUCT WEIGHT**

3 lbs / 1.4 kg

**SPECIFICATION LOGIC**

**DIFFUSER STYLE (GLOBE)**

Droplet	DD
Faceted	FF
Ribbed	RR

**PRIMARY FINISH COLOR**

Matte White	PC20
Silk Grey	PC25
Matte Black	PC30
Breccia	PC31
Vermilion	PC42
Custom Powder Coated	PCXX

**CCT**

2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

**DIMMING / CONTROL / INPUT**

0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	0.1_10V_UNV
1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	1_10V_UNV
1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	1_TRIAC_120V
10% Dimming, TRIAC / Forward Phase Control, 120V Input	10_TRIAC_120V
Low Voltage (Driver required, driver not included)	LV

**IP RATING**

IP 20	IP20
IP 65	IP65

**DRAWINGS**

Pastille dimensional drawings

