



PERFORMANCE

Delivered Lumens Est. 640 lm
 Power Consumption 8.5W
 90 CRI

CERTIFICATION

ADA Compliant
 UL Listed
 UL Listed to Canadian safety standards.
 Suitable for Wet Locations
 Suitable for Damp Locations
 IP20
 IP65

PATENT FILE NUMBER

US: D868,340

LED LIFESPAN

50k hours

Phase

Sconces

YOUR PRODUCT CODE

RGP-1- - - - -
 - - -

DESCRIPTION

Phase recalls a quarter of the lunar cycle, Earth's moon half lit. Half of this wall-mounted, cast-glass spherical sconce emits a bright light, while the other half is coated in a chrome finish for reduced output.

MATERIALS

Cast glass, anodized aluminum

COLLECTION NOTES

Each form of cast glass is unique. We review each to ensure they conform to ASTM standards, which includes the presence of small air bubbles within the glass.

PRODUCT DIMENSIONS

6 in dia x 4 in D

PRODUCT WEIGHT

2.5 lbs / 1.1 kg

SPECIFICATION LOGIC

BACKPLATE FINISH

Black Anodized AA04

COLOR TEMPERATURE

2700K (warm white) 27
 3000K (soft white) 30
 3500K (neutral white) 35

DIMMING / CONTROL / INPUT

High-Output, 1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External) 10_10V_UNV
 High-Output, 0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External) 0.1_10V_UNV
 10% Dimming, TRIAC / Forward Phase Control, 120V Input 10_TRIAC_120V
 1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External) 1_TRIAC_120V
 1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External) 1_10V_UNV
 0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External) 0.1_10V_UNV
 Low Voltage (Driver required, driver not included) LV

IP RATING

IP 20 IP20
 IP 65 IP65

DRAWINGS

RGP Phase Sconce Dimension

