



Ripple Sconce

Sconces

YOUR PRODUCT CODE

RP-WS- - - - - -
- - - - -

DESCRIPTION

Meet Ripple, a new sconce and flush mount collection distinguished by its substantial solid glass shade. A unique texture of raised, concentric rings brings to mind ripples coursing along the surface of water.

MATERIALS

Cast solid glass, aluminum

COLLECTION NOTES

Luminaire lumens listed are for DC input. AC input are within photometry downloads. Each form of cast glass is unique. We review each to ensure they conform to ASTM standards, which includes the presence of small air bubbles within the glass.

PRODUCT DIMENSIONS

5 in dia x 3.3 in D

PRODUCT WEIGHT

3.5 lbs / 2 kg

PERFORMANCE

Power Consumption 10W
90 CRI

Full detail in [photometry summary](#)

PATENT FILE NUMBER

US: U.S. patent application approved for issuance, CA: Patent Pending, CN: 202330243342.6, EU: 015019600-0001, 015019600-0002

CERTIFICATION

ADA Compliant
UL Listed
UL Listed to Canadian safety standards.
Suitable for Wet Locations
Suitable for Damp Locations
IP65
Declare (LBC Red List Approved)

Declare.

LED LIFESPAN

50k hours

SPECIFICATION LOGIC

GLASS FINISH

White Interior	S20
Smoked	S21
Frosted	S22
Copper Exterior	S23
Jade	S24

BACKPLATE FINISH

Natural Anodized	AA01
Black Anodized	AA04

COLOR TEMPERATURE

2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

DIMMING / CONTROL / INPUT

High-Output, 1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	10_10V_UNV
High-Output, 0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	0.1_10V_UNV
10% Dimming, TRIAC / Forward Phase Control, 120V Input	10_TRIAC_120V
1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	1_TRIAC_120V
1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	1_10V_UNV
0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	0.1_10V_UNV
Low Voltage (Driver required, driver not included)	LV

IP RATING

IP 65	IP65
-------	------

DRAWINGS

RP-WS Ripple Sconce Dimension (Rotate 90 degrees for flush mount version)

